

Foam-Matic 1.25 P / Foam-Matic 1.25 E

# Mobile foaming with excellent foam quality

max.  
44 psi

VITON

EPDM



1



- Transparent 1.5 litres (42 oz) plastic tank (ideal filling capacity for foaming: 16 oz)
- Chemical resistant Viton resp. EPDM gaskets
- Flexible suction hose (optimal residual spray drainage)
- Ergonomic and efficient hand pump up to 44 psi operation pressure
- Protected safety and relief valve
- Large filling opening
- Red for acids (Viton) – blue for alkalis (EPDM)



## Mobile foaming

Thanks to dry foam long contact- and reaction time is achieved. Saves mechanical cleaning effort and therefore time, energy and chemical. High air content results in good and dry foam. Therefore low chemical consumption (rough estimate: 3 oz foam liquid covers up to 16 ft<sup>2</sup> cleaning surface). Ideal for cleaning vertical surfaces and equipment.

### Additional advantages of foam cleaning with Foam-Matic 1.25 P/E

- Optimal surface coverage with excellent optical control
- Reduction of the aerosol mist in the air
- Optimal foam quality and easy use with flexible suction hose

### Convincing performance features!



**Foam-Matic 1.25 P**  
(Red = Acidic foaming agents)  
Art.No. 11976501



**Foam-Matic 1.25 E**  
(Blue = Alkaline foaming agents)  
Art.No. 11976601

Further products: [www.birchmeier.com](http://www.birchmeier.com)



Your Birchmeier distributor

Qspray.com (602) 371-1993